





SafeSite® Stainless Steel LED Linear Luminaire ATEX / IEXCEX Version



Emergency Version




Certifications

- Ex II 2GD e mb IIC T4 Gb (Ta = -20°C to +60°C)
- Ex tb IIIC T135°C Db (Ta = -20°C to +60°C)
- Certificate numbers: IECEx SIR12.0093
SIRA12ATEX3127
- ATEX Zones 1 & 21 and 2 & 22
- CE - Compliant with EN55015:2006 / EN61547:2009 / EN60598:2008
- IP 66/67 rated
- IK09 to EN 50102
- C & D shock compliant to MOD specification BR8470
- RoHS compliant

Features & Benefits

- L70 rated for > 100,000 hours @ 25°C ambient
- 5 year full performance warranty (Battery not included)
- Instant on/off operation
- Universal input (100-277V AC, 50/60Hz), (Emergency 230-240V AC or 110-120V AC, 50/60Hz)
- Superior colour rendition index compared to HPS, LPS, MV
- Mercury free
- Resistant to shock and vibration
- Easy retrofit solution for existing fluorescent fittings due to same size and fixing centres
- Factory safety shackle option available

Photometric Information



Application:

The Dialight SafeSite® LED Linear luminaire with its low profile, rugged design ensures long life and high reliability for a wide variety of Hazardous Area applications. Offered in 32W and 64W versions to replicate the light output of typical 2 x 18W & 2 x 36W fluorescent luminaires respectively, it is ideally suited for oil & gas, chemical, petro-chemical and other potentially explosive industrial environments. Dialight offers a range of mounting options for use with the SafeSite® Linear luminaire.

Mechanical Information

Fixture Weight:	
Standard Version:	1308mm - 11.4kg (25.1lbs) 708mm - 6.5kg (14.3 lbs)
Emergency Version:	1525mm - 14.5kg (32 lbs) 925mm - 9.1kg (19.8 lbs)
Shipping Weight:	
Standard Version:	1308mm - 14.2kg (31.3lbs) 708mm - 9.1kg (20 lbs)
Emergency Version:	1525mm - 17.5kg (38.6 lbs) 925mm - 11.3kg (25 lbs)
Shipping Dimensions:	1308mm - 240 x 160 x 1640 708mm - 240 x 160 x 1040
Mounting:	(2) M8 fixing points
Cable Entry:	2 x M20 cable entries at both ends, through wired as standard. Consult factory for other options

Electrical specifications

Operating Voltage	
Standard Version:	100-277V AC 50/60Hz
Emergency Version:	230-240V AC 50/60Hz or 110-120V AC 50/60Hz
Power Consumption:	See ordering information
Operating Temp:	-20°C to +60°C (-4°F to +140°F)
Noise Requirements/ EMC:	EN 61000-3-2: 2006
THD:	<15% @ 120 V AC <20% @ 230 V AC
Surge Protection:	EN-61000-4-5 1 kV line to line 2 kV line to ground
Power Factor:	> 0.9

Emergency Versions

Battery:	3.6V 10Ah NiMH
Expected Battery Life:	4 years
Battery duration:	> 180 Minutes

Materials

Housing and Fixings:	316 Marine grade stainless steel
Lens:	High Impact resistant polycarbonate
Mounting Brackets:	316L Stainless steel
Safety Shackle:	Optional factory fitted stainless steel safety shackle with 1.5 meter safety cord

Photometric Information

CCT:	5000K (cool white) 4000K (Neutral white)
CRI:	70 (cool white)
IES Files:	Consult factory

All values typical unless otherwise stated
All lumen values are typical (tolerance +/- 10%)





SafeSite® Stainless Steel LED Linear Luminaire

Ordering Information

Part Number	Voltage	Colour / CCT	Entry Options	Lumens	Watts	Lumens Per Watt
ELA-1C3R-SSCB	100 - 277V AC	5000K (cool white)	2 at each end	5,100	64	81
ELA-1N3R-SSCB	100 - 277V AC	4000K (Neutral white)	2 at each end	5,100	64	81
ELA-1C3M-SSCB	100 - 277V AC	5000K (cool white)	2 at each end	2,600	32	81
ELA-1N3M-SSCB	100 - 277V AC	4000K (Neutral white)	2 at each end	2,600	32	81
Emergency Version						
ELEA-1C4R-SSCB	230 / 240V AC	5000K (cool white)	2 at each end	5,100	70	73
ELEA-1N4R-SSCB	230 / 240V AC	4000K (Neutral white)	2 at each end	5,100	70	73
ELEA-1C5R-SSCB	110 / 120V AC	5000K (cool white)	2 at each end	5,100	70	73
ELEA-1N5R-SSCB	110 / 120V AC	4000K (Neutral white)	2 at each end	5,100	70	73
ELEA-1C4M-SSCB	230 / 240V AC	5000K (cool white)	2 at each end	2,600	35	74
ELEA-1N4M-SSCB	230 / 240V AC	4000K (Neutral white)	2 at each end	2,600	35	74
ELEA-1C5M-SSCB	110 / 120V AC	5000K (cool white)	2 at each end	2,600	35	74
ELEA-1N5M-SSCB	110 / 120V AC	4000K (Neutral white)	2 at each end	2,600	35	74


lm/W are under constant review and improvement, please consult technical department for latest achievable values
 For factory fitted safety shackle option, add 1 as a suffix to the part code. E.g ELA-1C3R-SSCB-1

Mounting Options & Accessories


	Part Number	Description	Kit Includes
	ELX-PC-SS-42	Ø40 - 45mm Range 316 Marine Grade Stainless Steel Pole Clamp	2 x Pole clamp bracket Mounting hardware
	ELX-PC-SS-47	Ø47 - 51mm Range 316 Marine Grade Stainless Steel Pole Clamp	
	ELX-PC-SS-54	Ø54 - 57mm Range 316 Marine Grade Stainless Steel Pole Clamp	
	ELX-PC-SS-59	Ø59 - 62mm Range 316 Marine Grade Stainless Steel Pole Clamp	
	ELX-EYE	316 Marine Grade Stainless Steel Eyelet kit	2 x M8 Eyelets Mounting Hardware
	ELX-CMB	316 Marine Grade Stainless Steel Ceiling Mount Kit	Bracket Mounting hardware
	ELX-WMB-SS-30	30° 316 Marine Grade Stainless Steel Wall Mount Kit	Bracket Mounting hardware
	ELX-WMB-SS-45	45° 316 Marine Grade Stainless Steel Wall Mount Kit	
	ELX-WMB-SS-60	60° 316 Marine Grade Stainless Steel Wall Mount Kit	
	ELX-WMB-SS-90	90° 316 Marine Grade Stainless Steel Wall Mount Kit	

Mounting Options & Accessory Dimensions


Pole Clamp




Eyelet




Ceiling Mount




Wall Mount Bracket 30°




Wall Mount Bracket 60°



Wall Mount Bracket 45°



Wall Mount Bracket 90°



Dialight reserves the right to make changes at any time in order to supply the best product possible. The most current version of this document will always be available at:

www.dialight.com/Assets/Brochures_And_Catalogs/Illumination/MDTFSSHZLSSEUX001.pdf. Warranty Statement: EXCEPT FOR THE WARRANTY EXPRESSLY PROVIDED FOR [HEREIN/ABOVE/BELOW], DIALIGHT DISCLAIMS ANY AND ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, TITLE, AND NON-INFRINGEMENT.